

# Product datasheet

Specifications



## APC Back-UPS Pro, 1500VA/ 865W, Tower, 230V, 6x 6A Indian outlets, AVR, LCD, User Replaceable Battery

BR1500G-IN

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V AC 1 phase
Plug standard	India 3-pin 16A
Input voltage limits	170...294 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	865 W
rated power in VA	1500 VA
Output connection type	4 India 3-pin 6A 2 India 3-pin 6A surge
USB Charging Port	None
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	865 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Efficiency	85 % (full load) 86 % (half load)
Output frequency	50/60 Hz +/- 1 Hz sync to mains

### Complementary

Battery type	Lead-acid battery
Additional information	9Ah x 2 internal batteries
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	7.2 h
Number of battery replacement quantity	1

<b>Battery life</b>	2...4 year(s)
<b>Battery charger power</b>	30 W rated
<b>Battery type</b>	Lead-acid internal included
<b>Control panel</b>	Multifunction LCD status and control console
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>UPS connectivity</b>	USB port
<b>Let through voltage rating</b>	330 V
<b>Surge energy rate</b>	680 J
<b>Cable length</b>	1.5 m
<b>Number of cables</b>	1
<b>Colour</b>	Black
<b>Height</b>	301 mm
<b>Width</b>	114 mm
<b>Depth</b>	382 mm
<b>Net weight</b>	11.76 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting mode</b>	Tower
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Range of product</b>	Back-UPS Pro
<b>Product or component type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product certifications</b>	BIS
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0...15240 m
<b>Relative humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %
<b>Acoustic level</b>	45 dBA
<b>Operating altitude</b>	0...10000 ft

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	38.1 cm

---

Package 1 Width	48.3 cm
Package 1 Length	22.9 cm
Package 1 Weight	13.19 kg
SCC14	10731304268793

---

## Contractual warranty

---

Warranty (in months) 24 UPS|12 Battery



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint 470

Environmental Disclosure [Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair No

## Use Again



### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No