

Product datasheet

Specifications



APC Easy UPS On-Line, 15kVA/
15kW, Rackmount 3U, 230V, 1x
Hard wire 3-wire(1P+N+E) outlet,
Intelligent Card Slot, No battery,
W/O rail kit

SRV15KUXI-IN

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase 400 V AC 3 phases
Input voltage	220 V 230 V 415 V
Input voltage limits	110...300 V half load 176...300 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Network frequency	40...70 Hz auto sensing
Output voltage	230 V AC 1 phase
Output voltage	220 V 240 V
Rated power in W	15000 W
rated power in VA	15000 VA
Output connector type	Hard wire 3-wire (1P + N + E) for 1 zone(s)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	2 %
Maximum configurable power in VA	15000 VA
Maximum configurable power in W	15000 W
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	95 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	External battery system
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Battery voltage	+/- 120 V
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery charger power	2340 W rated
Battery type	Lead-acid external sold separately
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rate	600 J
Number of rack unit	3U
Colour	Black (RAL 7010)
Height	130 mm
Width	438 mm
Depth	749 mm
Net weight	29 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with kit sold separately
Redundant	No
Range of product	Easy UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...60 °C
Storage altitude	0...15000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	65 dBA
Heat dissipation	2503 Btu/h
Operating altitude	0...3000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	87 cm
Package 1 Length	58 cm
Package 1 Weight	35.9 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 7095

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 080b8d64-796e-42e7-a17d-31b86e55d143

REACH Regulation [REACH Declaration](#)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

Image of product / Alternate images

Alternative



