

Product datasheet

Specifications



Device monitoring and management, Network Management Cards, NMC3 with Environmental Monitoring, secure remote UPS monitoring and management

AP9641

Overview

Lead time Usually in Stock

Main

Range of product	Network Management Cards
Range compatibility	Galaxy VM Galaxy VX Symmetra PX Easy UPS 3M Advanced Easy UPS 3-Phase Modular Galaxy PX Galaxy 3L Pro Smart-UPS Smart-UPS Ultra Smart-UPS Online Smart-UPS Modular Ultra Smart-UPS Battery Systems Back-UPS SX3 Refurbished Smart-UPS
Product or component type	Device monitoring and management
Provided equipment	Temperature sensor Micro-USB cable Installation manual
Number of input phases	1 3
Standards	EN 55024 BS EN 55024 EN 61000-4-2 BS EN 61000-4-2 EN 61000-4-3 BS EN 61000-4-3 EN 61000-4-4 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 EN 61000-4-6 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 EN 55035 BS EN 55035 EN 62040-2 BS EN 62040-2 EN 61326-2 BS EN 61326-2 ICES-003 class A VCCI class A EN 61000-6-3 BS EN 61000-6-3 EN 55032: class A BS EN 55032: class A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Variant option	Environmental monitoring
----------------	--------------------------

Physical

Net weight	0.09 kg
------------	---------

Width	12.1 cm
-------	---------

Height	3.8 cm
--------	--------

Depth	11.4 cm
-------	---------

Conformance

Product certifications	FCC Class A AS/NZS AS/NZS 3548 (C-Tick) class A FCC part 15 class A GOST UK PSTI
------------------------	---

Environmental

Storage Relative Humidity	0...95 %
---------------------------	----------

Relative humidity	0...95 %
-------------------	----------

Ambient air temperature for storage	-15...65 °C
-------------------------------------	-------------

Ambient air temperature for operation	-5...45 °C
---------------------------------------	------------

Storage altitude	0...15240 m
------------------	-------------

Operating altitude	0...10000 ft
--------------------	--------------

Communications & Management

Communication network type	10/100/1000BASE-T
----------------------------	-------------------

Authentication	Radius Lightweight Directory Access Protocol (LDAP)
----------------	--

Communication port protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP
-----------------------------	---

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	5.200 cm
------------------	----------

Package 1 Width	16.400 cm
-----------------	-----------

Package 1 Length	24.000 cm
------------------	-----------

Package 1 Weight	405.000 g
------------------	-----------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 123

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery Yes

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

