

Product datasheet

Specifications



APC Smart-UPS RC 1000VA, 230V, no battery, 4x India 3-pin 6A outlets

SRC1KUXI

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	India 3-pin 6A
Switching current capacity	10 A
Plug standard	India 3-pin 6A
Input voltage limits	110...280 V half load
Network frequency	40...70 Hz
Output voltage	230 V 1 phase
Output voltage	220 V 240 V
Rated power in W	800 W
Rated power in VA	1000 VA
Output connection type	4 India 3-pin 6A
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	90 % (full load) 88 % (half load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	External battery system
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery type	Lead-acid external sold separately
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

UPS connectivity	Serial port USB port
Cable length	1.5 m
Number of cables	1
Colour	Black
Height	220 mm
Width	145 mm
Depth	400 mm
Net weight	5.7 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Mounting mode	Tower
Provided equipment	Smart UPS signalling RS-232 cable User manual Warranty card
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	BIS
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...60 °C
Storage altitude	0...4572 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Operating altitude	0...3000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34 cm
Package 1 Width	47.8 cm
Package 1 Length	23.5 cm
Package 1 Weight	6.3 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 196

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number B2b22a56-41f2-497e-9ea6-cf093b3b8bd3

REACH Regulation [REACH Declaration](#)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

Image of product / Alternate images

Alternative



